

# LEITZ PRIMES

## TECHNICAL SPECIFICATIONS

<b>Focal Length (mm)</b>	18	21	25	29	35	40	50	65	75	100	135	180
<b>Aperture</b>	T 1.8											T 2
<b>Image Circle</b>	Vistavision (46.5 mm)											
<b>Close Focus (ft)</b>	1'2"	1'10"	1'10"	1'2"	1'6"	1'2"	1'7"	2'2"	2'6"	3'11"	3'11"	4'11"
<b>Close Focus (m)</b>	0.35	0.55	0.55	0.35	0.45	0.35	0.47	0.65	0.75	1.2	1.2	1.5
<b>Horizontal angle of view "Full Frame" 36 x 24 mm</b>	90.0°	81.2°	71.5°	63.7°	54.4°	48.5°	39.6	31.0°	27.0°	20.4°	15.2°	11.4°
<b>Horizontal angle of view "Super 35" 24.9 x 18.7 mm</b>	69.3°	61.3°	52.9°	46.5°	39.1°	34.6°	28.0°	21.7°	18.8°	14.2°	10.5°	7.9°
<b>Weight (lb)</b>	7.1	6.1	6.2	5.9	6.3	6.0	6.0	6.1	6.2	6.1	6.4	6.8
<b>Weight (kg)</b>	3.2	2.76	2.8	2.67	2.87	2.71	2.7	2.78	2.83	2.77	2.89	3.1
<b>Lenght (in / mm)</b>	7.9 / 201.5	7.2 / 183.7										7.9 / 201.5



Subject to change

<b>Lens Mount</b>	PL, LPL with Cooke/i metadata interface
<b>Front Diameter</b>	114 mm
<b>Front Filter</b>	M 112 x 1.5 mm screw-in
<b>Rear Filter</b>	Via net holder
<b>Matched Focus/Iris Ring Locations</b>	All focal lengths
<b>Focus Rotation</b>	270°
<b>Iris Rotation</b>	66°
<b>Focus scales</b>	Turnable scale, easy change from imperial to metric
<b>Iris Blades</b>	15
<b>Iris Shape</b>	Circular through all stops



Ernst Leitz Wetzlar GmbH  
 Am Leitz-Park 2 | 35578 Wetzlar | Germany  
[www.leitz-cine.com](http://www.leitz-cine.com) | [cc@leitz-cine.com](mailto:cc@leitz-cine.com)

輸入代理店  
 三友株式会社  
 〒141-0022 東京都品川区東五反田1-2-33白雉子ビル9F  
 営業事業部 システムビジネス営業部 03-6408-1452  
[www.mitomo.co.jp](http://www.mitomo.co.jp)